

# 803 TRANSFORMER





## Target Applications (not limited to)

- Manufacturing
- Construction
- Mining
- Electrical
- Medical







Certified Range		
SPH 5.00 to -5.00 [D]	CYL ±3.00 [D]	ADD 0.75 - 3.00

Eyres Difference	Benefits
Secure & fashionable fit	Wrap contour frame, ideal for a wide range of environments.
Ergonomic fit	Optimised comfort and protection, with a sleek design for all day wear.
Adaptable safety	Anti-slip nose and temple pads, and converts to low profile goggle.

SKU				Min PD	
803RX-GM-DL	59 mm	34 mm	19 mm	30 mm	118 mm
803RX-C1-DL	59 mm	34 mm	19 mm	30 mm	118 mm

Left Temple Marking	Right Temple Marking	Lens Marking
---------------------	----------------------	--------------

803RXGMDL |  | AUSTRALIA    Batch# |  AS/NZS 1337.6 | LIC.21598    Clear: RIO | Tinted: RI Cat.3 | Photo: RI Cat.0-3

803RXC1DL |  | AUSTRALIA    Batch# |  AS/NZS 1337.6 | LIC.21598    Clear: RIO | Tinted: RI Cat.3 | Photo: RI Cat.0-3