950 GULLWING

Target Applications (not limited to)

- Manufacturing
- Construction
- Mining
- Electrical
- Medical

Certified Range (6 base)			Certified Range (8 base)		
SPH 4.00 to -4.00 [D]	CYL ±3.00 [D]	ADD 0.75 - 3.00	SPH 3.50 to -3.50 [D]	CYL ±2.00 [D]	ADD 0.75 - 3.00

Eyres Difference	Benefits
Secure & fashionable fit	Wrap modular design for added flexibility in all environments.
Ergonomic fit	Optimised comfort and protection, with a sleek design for all day wear.
Adaptable safety	Anti-slip nose and temple pads, and made using thermo plastic for optimal fit.

SKU				Min PD	
950RX-M1-6BDL	56 mm	36 mm	20 mm	28 mm	114 mm
950RX-M1-8BDL	56 mm	36 mm	20 mm	30 mm	114 mm

Left Temple Marking	Right Temple Marking	Lens Marking
950RXM16BDL | EYRES | AUSTRALIA	Batch# | AS/NZS 1337.6 | LIC.21598	Clear: RIO | Tinted: RI Cat.3 | Photo: RI Cat.0-3
950RXM18BDL | EYRES | AUSTRALIA	Batch# | AS/NZS 1337.6 | LIC.21598	Clear: RIO | Tinted: RI Cat.3 | Photo: RI Cat.0-3